

SIGNS AND MARKINGS NOTES

1. All traffic sign and pavement marking installations shall be done in accordance with the "Manual of Uniform Traffic Control Devices for Streets and Highways," 1988 Edition, as amended, the latest specifications from the Traffic Review Branch, Department of Planning and Permitting and as shown on the plans.
2. The Contractor shall notify the Civil Engineering Branch, Department of Planning and Permitting, at 523-4881 to arrange for inspectional services and submit four (4) sets of approved Construction Plans seven (7) days prior to commencement of work.
3. The Contractor shall submit material brochures for all signs and paint materials to the Permitting and Inspection Section of the Civil Engineering Branch, Department of Planning and Permitting.
4. The signing and/or striping contractor shall keep one (1) set of approved plans at the project site at all times during construction work.
5. The Contractor shall paint temporary guidelines and outline of arrows, legends and crosswalks with a two (2) inch wide brushed line on the day of the roadway is opened to traffic. These markings must be approved by the Inspector from the Civil Engineering Branch, Department of Planning and Permitting.
6. The Contractor shall notify the Civil Engineering Branch, Department of Planning and Permitting at 523-4881, three (3) days in advance of final inspection.
7. The Contractor shall meet with the Inspector from the Civil Engineering Branch, Department of Planning and Permitting during the final inspection.
8. Within ten (10) days following notification of award of contract, the Contractor shall submit to the Permitting and Inspection Section, Civil Engineering Branch, Department of Planning and Permitting (523-4881) for approval, a list of any signing and pavement marking material, which he proposes to install. The list shall be complete as to the name of manufacturer, catalog number and shall be supplemented with material brochures.
9. Upon final inspection of the project, the Contractor shall submit a letter of certification for all traffic signing and pavement marking materials installed.
10. Signs shall be attached to brackets with 5/16" zinc plated steel bolts, nuts and washers. Signs 48" wide or larger than 10 square feet in area shall be mounted on two-2" galvanized pipe post. The sign shall be installed with at least one (1) foot clearance from the sign edge to the curb face.
11. All traffic signs shall be reflectorized.
12. Raised pavement markers shall be installed in accordance with the Department of Planning and Permitting standards.
13. Location of "STOP" sign:
 - A. Install "STOP" sign at curb tangent point.
 - B. Install "STOP" sign on metal street light standard if a standard is located within ten (10) feet of curb return.
 - C. Install "STOP" sign in front of utility pole if a pole is located within ten (10) feet of curb return.
14. Pavement word and symbol markings shall be in accordance with the Department of Planning and Permitting standards.
15. The Contractor shall use thermoplastic material, approved by the Permitting and Inspection Section of the Civil Engineering Branch, Department of Planning and Permitting, for all crosswalks, stop bars, pavement arrows, center lines, lane lines, arc lines, channelized traffic islands and legends.

c:\Desktop\Notes\TrafficSigns&Markings.doc